


BTP-3N

Mobile Receipt Printer



BTP-3N Specifications



Model	BTP-3N
Printing method	Direct thermal
Resolution	203 DPI
Line spacing	3.75mm (Adjustable by commands)
Print width	72 mm
Max.print speed	Max. 70 mm/s
Performance Features	
Interfaces	USB+Bluetooth(1+1)
Input buffer	128 Kbytes
NV Flash	4M Kbytes
Emulation	ESC/POS
Fonts/Graphics/Symbologies	
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) simplified/traditional Chinese: 3.0×3.0mm (24×24 dots)
Barcode types	1D: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/ CODE128 2D: QR CODE
Extended character sheet	PC347(Standard Europe) / Katakana/ PC850(Multilingual) /PC860(Portuguese) / PC863(Canadian-French)/ PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/ WPC1252/Pc866(Cyrillic#2) / PC852(Latin2)/ PC858/ IranII/ Latvian/ Arabic/ PT151(1251)
Rotation	0°, 90°, 180°, 270°
Physical characteristics	
Dimensions	135*105*61.5mm (L*W*H)
Gross weight	0.3kg
Compatible systems	
Systems	Windows/Android/iOS/Linux
Power supply	
Battery	7.4V/ 2000mAh (75 mtrs continuous print when fully charged)
Charging input	DC 5V/2A
Environmental Conditions	
Work environment	0 ~ 45°C, 10 ~ 80%RH no condensing
Storage environment	-10 ~ 60 °C, ≤10~90% RH no condensing



- Support missing paper alarm function



- Support QR CODE




70 mm/sec

- 70mm/s print speed



- 2000mAh battery



Scan QR code to checkout BTP-3N
Check Website for more information.
<https://www.ngxtechnologies.com>
Emai: enquiry@ngxtechnologies.com

